

# Eaton SC-60

Catalog Number: SC-60

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 60 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 10 kAIC at 300 Vdc|100 kAIC at 480 Vac, Standard, 480 V, 300 Vdc

## General specifications



Product Name	Catalog Number
Eaton Bussmann series SC fuse	SC-60
UPC	Product Length/Depth
051712250603	2.25 in
Product Height	Product Width
0.41 in	0.41 in
Product Weight	Warranty
0.35 lb	Not Applicable
Compliances	
CE Marked	
RoHS Compliant	

## Electrical rating

### Amperage Rating

60 A

### Interrupt rating

10 kAIC at 300 Vdc

100 kAIC at 480 Vac

### Response time

12 sec at 200%

### Voltage rating

480 Vac, 300 Vdc

## Physical details

### Packaging type

Standard

## General information

### Class

Class G

### Connection

Ferrule end x ferrule end

### Fuse indicator

Non-indicating

### Special features

Rejection style

## Resources

### Catalogs

Bussmann series complete full line catalog no. 1007

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

### Multimedia

Bussmann series Fuseology

### Specifications and datasheets

Eaton Specification Sheet - SC-60

### Technical data sheets

Bussmann series SC Class G Fuse Data Sheet No. 1024

SC-60~BUSS SC FUSE CLASS G CLASS G

### Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)